

Content provided by:

MATTERS

MFIB | MEMBERVANTAGE

Checklist: Walking & Working Surfaces

your NFIB membership and is provided by Markel, NFIB's preferred source for workers' compensation safety and loss control information.

This content is brought you as a benefit of

- Are permanent aisles and passageways appropriately marked and kept clear?
- Are load limit weights posted in the storage areas?
- Is adequate lighting provided in all work areas? (not an OSHA standard but a recommended practice)
- Is every open-sided floor or platform 4 feet or more above adjacent floor or ground level guarded by a standard guardrail or the equivalent?
- Are all hatchway and floor openings guarded?
- Are floor holes into which people can accidentally walk guarded?
- Are covers or guardrails provided to prevent people from falling into drainage ditches, open pits, vats, tanks, etc.?
- Are all fixed industrial stairways at least 22 inches wide?
- Are all fixed industrial stairways provided with a stair railing on all open sides?
- Are closed stairways provided with a railing on at least one side?
- Are all fixed stairways with a width in excess of 88 inches provided with a center stair railing?

- Is a 7-foot vertical clearance maintained above any stair tread?
- Are guardrails and toeboards provided on all open sides and ends of scaffolds more than 10 feet above the ground or floor?
- ☑ Are scaffolds and their components capable of supporting, without failure, at least four times the maximum intended load?
- Do all scaffold planks extend over end supports not less than 6 inches nor more than 18 inches?
- ☑ Are broken, bent, excessively rusted, altered or otherwise structurally damaged scaffold frames or accessories removed from service?

